


90° RPVC Bend



Description

90° bend in grey colour PVC (RAL 7035) with an index of protection IP44 for RPVC rigid conduits. Accessory is used for the assembly of PVC conduits by a push fit connection, creating a 90° bend.

Advantages

For connection of rigid RPVC conduits.

Protection index EN 60529: IP44.

Quick assembly via plug-in connection between conduits and fittings.

CE conformity to the 2014/35 directive and the EN IEC 61386 standard.

Made of PVC, not flame retardant.

Applications

Suitable for rigid PVC conduits in building, tertiary and industrial applications.

Solutions



Main technical characteristics

Colour	Grey RAL 7035	DN	NW16, NW20, NW25, NW32, NW40, NW50, NW63	M	PVC	IP	IP44	°C	-5 / 60 °C	Flame retardant
ETIM	10									
EC	000936									

Product data

DN		L _{mm}	Ref	kg/u	
NW16	19	70	55017016	0,009	25
NW20	23	90	55017020	0,013	25
NW25	29	120	55017025	0,031	25
NW32	36	150	55017032	0,045	10
NW40	40	292	80000030	0,248	
NW50	50	361	80000031	0,429	
NW63	63	424	80000032	0,629	

 Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

 Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic