

## RPVC Tee

1/2



### Description

Tee in grey colour PVC (RAL 7035) with an IP44 protection rating for RPVC rigid conduits. Accessory used for the assembly of PVC conduits by means of a push fit connection to the conduit, creating a two-way branch. With removable opening.

### Advantages

For connection of rigid RPVC conduits.

Protection index EN 60529: IP44.

Quick assembly via plug-in connection for conduits and accessories. It allows opening to access and manipulate the cables.

CE conformity to the 2014/35 directive and the EN IEC 61386 standard.

Made of PVC, not flame retardant.

### Applications

Suitable for rigid PVC conduits in building, tertiary and industrial applications.

### Solutions



[www.pemsa-rejiband.com](http://www.pemsa-rejiband.com)



Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

|                                                                                                       |                                                                                                             |                                                                                       |                                                                                        |                                                                                              |                                                                                                     |                     |
|-------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|---------------------|
|  Colour Grey RAL 7035 |  DN NW16, NW20, NW25, NW32 |  PVC |  IP44 |  -5 / 60 °C |  Flame retardant | ETIM 10<br>EC002922 |
|-------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|---------------------|

| DN   |  | L <sub>(mm)</sub> | A <sub>(mm²)</sub> | Ref.     | kg/u  |  |
|------|-----------------------------------------------------------------------------------|-------------------|--------------------|----------|-------|-------------------------------------------------------------------------------------|
| NW16 | 16.5                                                                              | 64                | 42                 | 55083016 | 0,010 | 25                                                                                  |
| NW20 | 20.5                                                                              | 76                | 50                 | 55083020 | 0,015 | 25                                                                                  |
| NW25 | 25.5                                                                              | 91                | 60                 | 55083025 | 0,022 | 25                                                                                  |
| NW32 | 30.5                                                                              | 108               | 72                 | 55083032 | 0,033 | 15                                                                                  |

- CU** - Copper electroplated
- PG** - Pregalvanised
- EZ** - Electrogalvanised
- BC** - Electrogalvanised Bichromate
- BK8** - High Resistance Coating
- GC** - Hot Dip Galvanising
- INOX** - Stainless Steel
- PT** - Polyester Paint
- AL** - Aluminum
- LN** - Brass or Nickel-plated brass

**PC+ABS** - Halogen Free Polycarbonate + ABS

**PVC** - Polyvinyl Chloride

**PP** - Halogen Free Polypropylene

**PA6** - Halogen Free Polyamide 6

**PA12** - Halogen Free Polyamide 12

**PU** - Polyurethane

**PE** - Polyethylene

**NBR** - NBR rubber

**PET** - Thermoplastic Polyester

**TPV** - Thermoplastic

