

Medium Duty Cantilever M-Plus (Ref: 82003777)

1/2



Description

Multipurpose cantilever for fixing Rejiband®, Pemsaband® and Megaband® cable trays in wall mounting, wall mounting on rail, or in ceiling mounting installed through reinforced cantilever arms. Width 200 mm, With AZ+ protection system, ZM finish

Advantages

In accordance with the IEC 61537 and CE standard with respect to directive 2014/35 / EU.

Available in PG, Pre-galvanized and AZ+, High-resistance alloy corrosion protection systems.

Universal mounting system compatible with Rejiband® wire mesh trays, Pemsaband® sheet trays and Megaband® ladder. A single support for all trays and ladder. Reduction in the number of references.

Applications

Suitable for Spiderband® cable suspension installations, for Rejiband® wire mesh trays, Pemsaband® sheet trays and other items such as luminaires, pipes, air conditioning, signage, etc. Recommended for indoor installations.

Solutions



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



Product data

ETIM 10	EC001003	u	1
Huella de CO2. GWP A1-A3 (kg CO2 eq.)	0,817	Material	Steel with surface coating
Protection System	AZ+	Working temperature range (°C)	-50 / 150 °C
Finish	ZM High Resistance Alloy	Fire resistance	A1 No combustible
Resistance Class	Class 8		
Width (mm)	200		
kg/u	0,253		

🔩 Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

🔧 Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic