





Description

41x41mm horizontal support for wall fixing of cable trays, electrical conduits and other heating pipe installations, A/C, fire protection systems, etc. Width 200 mm, With INOX protection system, I316L finish. Excellent loading capacity. Robust and secure system. Made of steel, available in various protection systems.

Advantages

Available in GC Protection Systems and INOX, Stainless steel AISI 304 and AISI 316L

Available in widths from 200 to 1000 mm depending on the protection system. It has wide fixing options.

This range of Cantilever arms 41 has a quick installation solution when using the Strut clip, part number 67030049, making it a quick and safe installation option for Rejiband® wire mesh trays.

The total length of the support is: (cable tray width + 55mm), that is, it has an additional measure of length to favor the separation of the installation from the facing or surface.

Load values according to international standard IEC 61537.

Applications

Application as a horizontal wall support. For supporting Cable Trays (rejiband®, pemsaband®, megaband®, among others) but it is also very useful for supporting electrical conduits and other heating pipe installations, A/C, fire systems etc.

Solutions



Product data

ETIM 10	EC001003	u	1
Huella de CO2. GWP A1-A3 (kg CO2 eq.)	4,052	Material	Acero inoxidable AISI 316L
Protection System	INOX	SWL (kg)	358
Finish	Stainless Steel AISI 316L	Working temperature range (°C)	-25 / 105 °C
Resistance Class	Class 9D	Fire resistance	E90 (90 min. 1000°C)
Width (mm)	200		
kg/u	0,763		

🔒 Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

🧊 Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene


NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic



Load diagrams

↓CTA↓ (kg)		kg
	200	358
	300	262
	500	165
	600	141
	800	107
	1000	85


Product applications





www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."







↓CTA↓ (kg)		kg
	200	358
	300	262
	500	165
	600	141
	800	107
	1000	85

