

Cantilever Arm Brace**Description**

Reinforcement accessory for 41 channel pendulum bracket that acts as support and allows you to achieve a more resistant support system. Made from steel, available in various protection systems.

Advantages

It allows to achieve a more reinforced support system.

Fixing with M6, M8 and M10 screws.

Load values according to international standard IEC 61537.

Available in GC Protection Systems and INOX, Stainless steel AISI 316L

In accordance with CE standard with respect to directive 2014/35 / EU.

Applications

Application as a vertical ceiling support. For supporting Cable Trays (rejiband®, pemsaband®, megaband®, among others) but it is also very useful for supporting electrical conduits and other heating pipe installations, A/C, fire systems etc.

Solutions

Cantilever Arm Brace

Main technical characteristics

 5	 -25 / 105 °C	 A1 No combustible	ETIM 10 EC001003
--	--	---	---------------------

Product data

				
GC	Class 6	82002627	1,744	Steel with surface coating
INOX	Class 9D	82002628	1,714	Acero inoxidable AISI 316L

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic



Cantilever Arm Brace

Product applications

