


Metatray insulating divider (Ref: 82003661)



Description

Advantages

Applications

Solutions



Product data

ETIM 10	EC001000	Material	PVC
Huella de CO2. GWP A1-A3 (kg CO2 eq.)	0,001	Impact Strength (J)	6 J
Colour	Grey RAL 7035	Working temperature range (°C)	-20 / 60 °C
Flange (mm)	60	Fire resistance	GRADO UL94: V0
Length (m)	3	UV Behaviour	Resistant acc. to UL568
kg/u	0,430		
u	30		

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic



Product applications

