


**Outside Riser Cover Click** ( Ref: 73026600 )



**Description**

Metal cover for the protection of cables in the 90° Click Outside Riser. Width 600 mm, With PG protection system, PG3 finish. It has a press-fit assembly system. Made of steel and available in various sizes and Protection Systems.

**Advantages**

The ends have an overlap to improve the fit with straight lids.

Available in all sizes and protection systems: PG, GC and stainless steel AISI304 and AISI316.

Press-fit click system requiring no additional parts.

**Applications**

It is used for the protection of wiring in the installation of Pemsaband® One perforated and solid tray installations where the 90° Click Outside Riser is used for installations in public buildings, infrastructures and civil works, tertiary sector and industrial applications.

**Solutions**



| Product data                          |  |                            |  |
|---------------------------------------|--|----------------------------|--|
| ETIM 10                               |  | EC002402                   |  |
| Huella de CO2. GWP A1-A3 (kg CO2 eq.) |  | 4,457                      |  |
| Protection System                     |  | PG                         |  |
| Finish                                |  | PG3, Pregalvanised         |  |
| Resistance Class                      |  | Class 3                    |  |
| Width (mm)                            |  | 600                        |  |
| R (mm)                                |  | 100                        |  |
| kg/u                                  |  | 1,380                      |  |
| u                                     |  | 1                          |  |
| Material                              |  | Steel with surface coating |  |
| Working temperature range (°C)        |  | -50 / 150 °C               |  |
| Fire resistance                       |  | A1 No combustible          |  |

| Protection System                 |
|-----------------------------------|
| CU - Copper electroplated         |
| PG - Pregalvanised                |
| EZ - Electrogalvanised            |
| BC - Electrogalvanised Bichromate |
| BK8 - High Resistance Coating     |
| GC - Hot Dip Galvanising          |
| INOX - Stainless Steel            |
| PT - Polyester Paint              |
| AL - Aluminum                     |
| LN - Brass or Nickel-plated brass |

| Insulating materials                      |
|-------------------------------------------|
| PC+ABS - Halogen Free Polycarbonate + ABS |
| PVC - Polyvinyl Chloride                  |
| PP - Halogen Free Polypropylene           |
| PA6 - Halogen Free Polyamide 6            |
| PA12 - Halogen Free Polyamide 12          |
| PU - Polyurethane                         |
| PE - Polyethylene                         |
| NBR - NBR rubber                          |
| PET - Thermoplastic Polyester             |
| TPV - Thermoplastic                       |