



Description

Advantages

Applications

Solutions



Product data

ETIM 10	EC000940	kg/u	0,003
Huella de CO2. GWP A1-A3 (kg CO2 eq.)		u	50
Protection System	LTN	Material	Nickel-plated brass
Finish	Nickel-plated brass	Working temperature range (°C)	-60 / 200 °C
M/PG	PG11	Fire resistance	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA
G (mm)	3.5		
Torque wrench	21		

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

