




Description

AISI303, 304 stainless steel metal nut, with metric and PG thread for connection of stainless steel conduits, connectors and metal cable glands.

Advantages

Compatible with metric or PG metal threaded fittings for all ranges of stainless steel conduit and glands.

Working temperature: -45°C to + 150°C.

CE conformity to the 2014/35 directive and the EN IEC 61386 standard.

Manufactured in stainless steel AISI 303, 304, (standard EN 10088), with Thermicron passivation treatment, suitable for installations in aggressive environments. Grade 4 corrosion resistance, according to IEC 61386. High indoor and outdoor protection.

Applications

Suitable for connection of threaded fittings of all ranges of rigid, flexible and metal conduits and metal cable glands for the management of electrical cables in building and industrial applications.

Solutions



Main technical characteristics

INOX M12, M16, M20, M25, M32, M40, M50, M63, PG 7, PG 9, PG11, PG13, PG16, PG21, PG29, PG36, PG42, PG48

LIBRE DE HALÓGENOS, NO PROPAGADOR DE LA LLAMA ETIM 10 EC000940

Product data

			Ref	kg/u			
M12	2.8	15	40014120	0,002	20	Stainless steel AISI 303	-60 / 200 °C
M16	2.8	19	40014160	0,003	20	Stainless steel AISI 304	-45 / 150 °C
M20	3	24	40014200	0,004	20	Stainless steel AISI 304	-45 / 150 °C
M25	3.5	30	40014250	0,009	10	Stainless steel AISI 304	-45 / 150 °C
M32	3.5	36	40014320	0,011	10	Stainless steel AISI 304	-45 / 150 °C
M40	5	46	40014400	0,019	5	Stainless steel AISI 304	-45 / 150 °C
M50	5	57	40014500	0,026	5	Stainless steel AISI 304	-45 / 150 °C
M63	6	70	40014630	0,055	5	Stainless steel AISI 304	-45 / 150 °C
PG 7	2.8	15	40015007	0,002	20	Stainless steel AISI 303	-60 / 200 °C
PG 9	2.8	18	40015009	0,002	10	Stainless steel AISI 303	-60 / 200 °C
PG11	3	22	40015011	0,003	10	Stainless steel AISI 303	-60 / 200 °C
PG13	3	24	40015013	0,004	10	Stainless steel AISI 303	-60 / 200 °C
PG16	3	27	40015016	0,005	10	Stainless steel AISI 303	-60 / 200 °C
PG21	3.5	32	40015021	0,008	10	Stainless steel AISI 303	-60 / 200 °C
PG29	4	41	40015029	0,010	10	Stainless steel AISI 303	-60 / 200 °C
PG36	5	50	40015036	0,018	5	Stainless steel AISI 303	-60 / 200 °C
PG42	5	60	40015042	0,033	5	Stainless steel AISI 303	-60 / 200 °C
PG48	5.5	65	40015048	0,036	5	Stainless steel AISI 303	-60 / 200 °C

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



TCM-INOX Nut

- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic

