



Description

Halogen-free aluminium clip for the fixing of RAL conduits in installations that require an excellent degree of resistance to corrosion and high mechanical performance. Accessory for mounting rigid conduits with fixing by pressure. Available for various conduit sizes.

Advantages

Accessory for the assembly of rigid pipes with fixing of the tube by means of pressure. Lightweight and easy to install.

CE conformity to the 2014/35 directive and the EN IEC 61386 standard.

Available in various sizes: NW16, NW20, NW25, NW32 and NW40.

Made of aluminum, suitable for installations in industrial plants and aggressive environments. Grade 4 corrosion resistance, according to IEC 61386. High indoor and outdoor protection.

Working temperature: -45°C to + 250°C.

Applications

It is recommended for RAL aluminium conduits in installations that require high mechanical performance. With a high resistance to corrosion in applications of industrial plants, tertiary and industrial sector with high safety requirements. Premises with risk of fire or explosion. Installation outside and in aggressive environments.

Solutions



Product data			
ETIM 10		EC000368	
Huella de CO2. GWP A1-A3 (kg CO2 eq.)			
Protection System		AL	
Finish		ALU, Aluminium	
DN		NW25	
kg/u		0,013	
		u	
		50	
		Material	
		Aluminum	
		Working temperature range (°C)	
		-45 / 250 °C	
		Fire resistance	
		LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA	

Protection System

CU

- Copper electroplated

PG

- Pregalvanised

EZ

- Electrogalvanised

BC

- Electrogalvanised Bichromate

BK8

- High Resistance Coating

GC

- Hot Dip Galvanising

INOX

- Stainless Steel

PT

- Polyester Paint

AL

- Aluminum

LN

- Brass or Nickel-plated brass

Insulating materials

PC+ABS

- Halogen Free Polycarbonate + ABS

PVC

- Polyvinyl Chloride

PP

- Halogen Free Polypropylene

PA6

- Halogen Free Polyamide 6

PA12

- Halogen Free Polyamide 12

PU

- Polyurethane

PE

- Polyethylene

NBR

- NBR rubber

PET

- Thermoplastic Polyester

TPV

- Thermoplastic