





Description

Conduit end support of self-extinguishing, halogen-free polyamide 12 available in various sizes. It is used in conjunction with clamps and has tabs for the correct fastening of RB-PA and RB-PU conduits in Robotics applications.

Advantages

Manufactured in polyamide 12. Self-extinguishing, halogen-free and flame-retardant.

Fixing the end of the tube together with clamps in robot joints.

Working temperature: -25°C to + 90°C.

It has tabs for the correct attachment of RB-PA and RB-PU flexible conduits.

CE conformity to the 2014/35 directive and the IEC 61386 standard.

Applications

Suitable for Robotics and wiring installations for robot arms in assembly lines, industrial applications, etc.

Solutions



Main technical characteristics

ETIM 10

Product data

COLOUR	DN	REF	kg/u				
Black RAL 9005	NW70	33110170	0,039	10	Poyamide 12	-25 °C	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA

 Protection System

- CU** - Copper electroplated
- PG** - Pregalvanised
- EZ** - Electrogalvanised
- BC** - Electrogalvanised Bichromate
- BK8** - High Resistance Coating
- GC** - Hot Dip Galvanising
- INOX** - Stainless Steel
- PT** - Polyester Paint
- AL** - Aluminum
- LN** - Brass or Nickel-plated brass

 Insulating materials

- PC+ABS** - Halogen Free Polycarbonate + ABS
- PVC** - Polyvinyl Chloride
- PP** - Halogen Free Polypropylene
- PA6** - Halogen Free Polyamide 6
- PA12** - Halogen Free Polyamide 12
- PU** - Polyurethane
- PE** - Polyethylene
- NBR** - NBR rubber
- PET** - Thermoplastic Polyester
- TPV** - Thermoplastic