





Description

Conduit end support of self-extinguishing, halogen-free polyamide 12 available in various sizes. It is used in conjunction with clamps and has tabs for the correct fastening of RB-PA and RB-PU conduits in Robotics applications.

Advantages

CE conformity to the 2014/35 directive and the IEC 61386 standard.

It has tabs for the correct attachment of RB-PA and RB-PU flexible conduits.

Manufactured in polyamide 12. Self-extinguishing, halogen-free and flame-retardant.

Fixing the end of the tube together with clamps in robot joints.

Working temperature: -25°C to + 90°C.

Applications

Suitable for Robotics and wiring installations for robot arms in assembly lines, industrial applications, etc.

Solutions



Product data

ETIM 10		Material	Poyamide 12
Huella de CO2. GWP A1-A3 (kg CO2 eq.)		Working temperature range (°C)	-25 °C
Colour	Black RAL 9005	Fire resistance	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA
DN	NW70		
kg/u	0,039		
u	10		

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

