


90° RINOX Bend (Ref: 55013032)

1/2



Description

90° push fit bend in stainless steel AISI 304 with IP54 protection rating for the connection of RINOX pipes in installations that require an excellent degree of corrosion resistance and high mechanical performance. Available in different diameters.

Advantages

Suitable for aesthetic applications.

Push-in type connection with RINOX sleeves for connection to RINOX conduits.

CE conformity to the 2014/35 directive and the EN IEC 61386 standard.

Manufactured in stainless steel AISI 303, 304, (standard EN 10088), with Thermicron passivation treatment, suitable for installations in aggressive environments. Grade 4 corrosion resistance, according to IEC 61386. High indoor and outdoor protection.

Working temperature: -45°C to + 250°C. Degree of protection IP54 according to classification EN60529.

Applications

It is recommended for RINOX pipes in installations that require an excellent degree of resistance to corrosion and high mechanical performance. For the management of cables in industrial plants, especially food, beverage and agricultural industries.

Solutions



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



Product data

ETIM 10	EC000936	u	5
Huella de CO2. GWP A1-A3 (kg CO2 eq.)		Compression strength (N)	1250 N
Protection System	INOX	Impact Strength (J)	6 J
DN	NW32	IP	IP44
Ø d1 (mm)	32	Working temperature range (°C)	-45 / 250 °C
R (mm)	95	Fire resistance	LIBRE DE HALÓGENOS, NO PROPAGADOR DE LA LLAMA
L (mm)	220		
kg/u	0,282		

Protection System

- CU** - Copper electroplated
- PG** - Pregalvanised
- EZ** - Electrogalvanised
- BC** - Electrogalvanised Bichromate
- BK8** - High Resistance Coating
- GC** - Hot Dip Galvanising
- INOX** - Stainless Steel
- PT** - Polyester Paint
- AL** - Aluminum
- LN** - Brass or Nickel-plated brass

Insulating materials

- PC+ABS** - Halogen Free Polycarbonate + ABS
- PVC** - Polyvinyl Chloride
- PP** - Halogen Free Polypropylene
- PA6** - Halogen Free Polyamide 6
- PA12** - Halogen Free Polyamide 12
- PU** - Polyurethane
- PE** - Polyethylene
- NBR** - NBR rubber
- PET** - Thermoplastic Polyester
- TPV** - Thermoplastic

