



Description

AISI 304 stainless steel push fit coupler for the connection of RINOX conduits in installations that require high mechanical performance and excellent resistance to corrosion. IP44 protection index. Available in different sizes.

Advantages

Suitable for aesthetic applications.

CE conformity to the 2014/35 directive and the EN IEC 61386 standard.

Manufactured in stainless steel AISI 303, 304, (standard EN 10088), with Thermicron passivation treatment, suitable for installations in aggressive environments. Grade 4 corrosion resistance, according to IEC 61386. High indoor and outdoor protection.

Working temperature: -45°C to + 250°C. Degree of protection IP44 according to classification EN60529.

Push fit type connection for joining conduits or accessories.

Applications

It is recommended for joining RINOX pipes in installations that require an excellent degree of resistance to corrosion and high mechanical performance. For the management of cables in industrial plants, especially food, beverage and agricultural industries.

Solutions



Product data

ETIM 10	EC000939	kg/u	0,021
Huella de CO2. GWP A1-A3 (kg CO2 eq.)		u	5
Protection System	INOX	Material	Stainless steel AISI 304
Finish	Stainless Steel AISI 304	IP	IP44
DN	NW20	Working temperature range (°C)	-45 / 250 °C
G (mm)	24	Fire resistance	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA
Ø d2 (mm)	21.7		
L (mm)	50		

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

