



### Description

Push fit Tee with removable cover for the connection of RL conduits in installations requiring high mechanical performance and medium resistance to corrosion. With an IP54 protection index. Accessory to create a branch in the conduit run. Made of aluminium and available in different diameters.

### Advantages

Compatible with rigid RAL aluminum conduits, for installations requiring high resistance to corrosion.

CE conformity to the 2014/35 directive and the EN IEC 61386 standard.

Made of cast aluminum. Grade 4 corrosion resistance, according to IEC 61386. High indoor and outdoor protection.

Protection index EN 60529: IP54.

Push fit connection system. Accessory to create branches in the routing of cable conduits.

### Applications

Suitable for the connection of rigid RL and RAL metal conduits in building, tertiary and industrial applications with high safety requirements. Premises of public attendance and premises with risk of fire or explosion.

### Solutions



Product data

|                                       |                |                                |                                              |
|---------------------------------------|----------------|--------------------------------|----------------------------------------------|
| ETIM 10                               | EC002922       | kg/u                           | 0,567                                        |
| Huella de CO2. GWP A1-A3 (kg CO2 eq.) |                | u                              | 1                                            |
| Protection System                     | AL             | Material                       | Aluminum                                     |
| Finish                                | ALU, Aluminium | IP                             | IP54                                         |
| DN                                    | NW50           | Working temperature range (°C) | -45 / 400 °C                                 |
| G (mm)                                | 43.5           | Fire resistance                | LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA |
| L (mm)                                | 183            |                                |                                              |
| A (mm)                                | 120            |                                |                                              |
| B (mm)                                | 61.5           |                                |                                              |

Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic