


Description

Rigid GC Protection System steel conduit. Especially suitable for installations that require high mechanical performance and high resistance to corrosion. IP54 protection index. Available in different diameters and supplied in 3 metre lengths.

Advantages

High mechanical performance.

CE conformity to the 2014/35 directive and the EN IEC 61386 standard.

Manufactured in GC protection system steel (standard EN ISO 1461), suitable for outdoor installations and in aggressive environments. Grade 4 corrosion resistance, according to IEC 61386. High indoor and outdoor protection.

Compression resistance: 1250 N. Impact Resistance: Grade 4.

Push fit type connection for joining conduits or accessories.

Applications

Its use is recommended in installations that require high mechanical performance and high resistance to corrosion in building, tertiary and industrial applications with high safety requirements. Premises of public attendance or with risk of fire or explosion. Also for outdoor installation and aggressive environments.

Solutions



METAL System. Metal Rigid Conduits

11/10/2026

RLGC Rigid Conduit (Ref: 13040163)

2/3



ENERGY



www.pemsa-rejiband.com



Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

ETIM 10	EC001173	Material	Steel with surface coating
Huella de CO2. GWP A1-A3 (kg CO2 eq.)		Cod. IEC.61386	4457
Protection System	GC	Compression strength (N)	1250 N
Finish	HDG, Hot Dip Galvanised	Impact Strength (J)	6 J
DN	NW63	IP	IP54
Ø d1 (mm)	60.6	Working temperature range (°C)	-45 / 400 °C
Ø d2 (mm)	63	Fire resistance	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA
kg/u	2,561		
u	15		

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Reijband, Pemsaband, Inducanal, Reijtech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

