



Description

EZ Protection System steel push fit coupler for the connection of RL conduits in installations that require high mechanical performance and medium resistance to corrosion. IP54 protection index. N mark of Aenor according to IEC 61386 standard.

Advantages

CE conformance with the directive 2014/35 and the IEC 61386 standard. N mark of Aenor according to IEC 61386.

Manufactured in PG protection system (standard EN-ISO 2081), suitable for indoor installations. Anti-corrosive interior primer. Grade 2 corrosion resistance, according to IEC 61386. Medium indoor and outdoor protection.

Protection index EN 60529: IP54.

Working temperature: -45°C to + 400°C.

Push fit type connection for joining RL conduits or accessories.

Applications

Suitable for the joining of RL plug-in rigid metal conduits in building, tertiary and industrial applications with high safety requirements. Premises of public attendance and premises with risk of fire or explosion.

Solutions



Product data

ETIM 10	EC000939	kg/u	0,035
Huella de CO2. GWP A1-A3 (kg CO2 eq.)		u	25
Protection System	EZ	Material	Steel with surface coating
Finish	EZ2, Electrogalvanised	IP	IP54
DN	NW25	Working temperature range (°C)	-45 / 400 °C
G (mm)	26	Fire resistance	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA
Ø d2 (mm)	27.1		
L (mm)	55		

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

