



Description

GC Protection System steel push fit coupler for the connection of RRGC conduits in installations that require high mechanical performance and high resistance to corrosion. IP54 protection index. Available in different diameters.

Advantages

CE conformity to the 2014/35 directive and the EN IEC 61386 standard.

Manufactured in GC protection system steel (standard EN ISO 1461), suitable for outdoor installations and in aggressive environments. Grade 4 corrosion resistance, according to IEC 61386. High indoor and outdoor protection.

Protection index EN 60529: IP54.

Working temperature: -45°C to + 400°C.

Threaded connection for joining conduits or accessories.

Applications

It is recommended for joining the RRGC conduit in installations that require high mechanical performance. With a high resistance to corrosion in building applications, tertiary and industrial sectors with high safety requirements. Premises of public attendance or with risk of fire or explosion. Installation outside and in aggressive environments.

Solutions



Product data

ETIM 10	EC000939	kg/u	0,034
Huella de CO2. GWP A1-A3 (kg CO2 eq.)		u	50
Protection System	GC	Material	Steel with surface coating
Finish	HDG, Hot Dip Galvanised	IP	IP65
DN	NW20	Working temperature range (°C)	-45 / 400 °C
M/PG	M20	Fire resistance	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA
Ø d2 (mm)	22.3		
L (mm)	30		

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

