


ST-PA Halogen Free Flexible Conduit (Ref:

1/2

10041029)



Description

Flexible corrugated conduit, made of self-extinguishing polyamide 6 in grey RAL 7031 or black RAL 9005, halogen-free according to EN 50642 standard and with an IP67 protection rating. The ST-PA flexible conduit of the Pemsaflex® range is recommended for industrial applications, machinery and where a high degree of flexibility and excellent weathering and UV radiation are required. ULf1 classified according to UL746C and EN ISO 4892-2.

Advantages

Manufactured in polyamide 6. Self-extinguishing, halogen-free according to UNE/EN 60754-2 y UNE/EN 60754-1 and flame-retardant.

Protection index EN 60529: IP67 with the suitable fittings.

Halogen-free according to EN 50642 /EN IEC 63355

Impact resistance. Grade 4, 6 Joules.

Working temperature: -40°C to + 105°C.

Applications

It is recommended for use in industrial applications and electrical installations of machine tools, robot equipment and vehicles. Excellent resistance against fats, alcohols, oils and lubricants and superb behaviour in outdoor applications. Resistant to UV radiation.

Solutions



RAILWAY APPLICATIONS



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



Product data			
ETIM 10		EC001175	
Huella de CO2. GWP A1-A3 (kg CO2 eq.)			
Colour		Black RAL 9005	
DN		NW29	
Ø d1 (mm)		28.2	
Ø d2 (mm)		34.4	
R (mm)		50	
kg/u		0,135	
u		25	
Material		Polyamide 6	
Cod. IEC.61386		24234	
Compression strength (N)		320 N	
Impact Strength (J)		6 J	
IP		IP67	
Working temperature range (°C)		-40 / 105 °C	
Fire resistance		Flame retardant	
UV Behaviour		ULf1 Resistant	

Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic