



Description

Metal accessory with welded safety edge, for creating a Tee at any point in the Megaband® REP ladder. Assembly using bolts. Bend radius 300mm. Check availability of 600mm radius. Made from steel with GC Protection system.

Advantages

Allows cable installation to be branched from one to two separate wiring lines.

Specially designed for the petrochemical sector, with REPSOL approvals, ED-P-11-02

Conforms to IEC 61537 and CE Conformity to Directive 2014/35/EU.

GC Protection System. Hot dip Galvanised with 85 microns of thickness. Class 8 according to IEC 61537.

Applications

Suitable for creating tees with Megaband® REP ladder for the distribution of cables in electrical and telecommunications installations in public buildings, infrastructures and civil works, industrial installations and the service sector when supporting very high loads.

Solutions



Main technical characteristics

 GC	 Class 8	 70, 100, 120	 100, 200, 300, 400, 600	 300	 1	 Steel with surface coating	 20 J
 -50 / 150 °C	 A1 No combustible	ETIM 10 EC001540					

Product data

		Ref	kg/u
70	100	82002428	9,480
70	200	82002429	12,200
100	300	82002430	16,300
100	400	82002431	17,900
120	600	82002432	24,400

Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic