




Description

Metal accessory for creating a Tee at any point in the Nemaband® ladder. Allows the creation of a Tee in the cable path. Check availability of 900mm radius. Made from steel with GC Protection system.

Advantages

Reinforced profiles in C and Z formats that stiffen the construction of the cable ladder, to meet the demand in most markets.

Allows cable installation to be branched from one to three separate wiring lines.

Cable tray connection using M8 screws or Nemaband® M8 joint kit

CE certified in compliance with the low voltage directive 2014/35 / EU

GC Protection System. Hot dip Galvanised with 85 microns of thickness. Class 8 according to IEC 61537.

Applications

Suitable for the creation of tee's with Nemaband® ladder for routing, protecting and distributing cables in electrical installations in industrial applications and large spans in: Oil & Gas and Petrochemical Industry, Power Plants, Electric Power Plants, etc. Water Treatment, Mining and Cement Offshore Platforms, Ports, Maritime Applications. Industrial projects in aggressive environments.

Solutions



Main technical characteristics

 GC	 Class 8	 100, 150	 150, 300, 450, 600, 750, 900	 1	 Steel with surface coating	 20 J
 -50 / 150 °C	 A1 No combustible	ETIM 10 EC001540				

Product data

			Ref	kg/u
100	150	300	82002845	7,130
100	300	300	82002846	8,380
100	450	300	82002847	12,100
100	600	300	82002848	13,800
100	750	300	82002849	17,300
100	900	300	82002850	18,900
150	150	300	82002851	9,310
150	300	300	82002852	10,700
150	450	300	82002853	14,500
150	600	300	82002854	16,300
150	750	300	82002855	20,000
150	900	300	82002856	21,700
100	150	600	82002857	10,400
100	300	600	82002858	12,000
100	450	600	82002859	18,000
100	600	600	82002860	20,300
100	750	600	82002861	23,700
100	900	600	82002862	25,600
150	150	600	82002863	13,600
150	300	600	82002864	16,000
150	450	600	82002865	21,500
150	600	600	82002866	23,900
150	750	600	82002867	27,400
150	900	600	82002868	29,500

Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum

LN - Brass or Nickel-plated brass

 Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

