


Hexagonal Set Screw M10



Description

Bolt with hexagonal head, M10x20 and M10x35 for fixing joints, supports and channel structures for Nemaband® ladder installations. Made from steel with GC Protection system.

Advantages

Fixing accessory with high clamping capacity for installations of cable trays, supports and channel structures.

Versatile piece for using in any coupler element with M8 hexagonal nut.

Improves the seal of the fitting or cable gland on the box, reaching IP67.

In accordance with CE standard with respect to directive 2014/35 / EU.

GC Protection System. Hot dip Galvanised with 85 microns of thickness. Class 8 according to IEC 61537.

Applications

Suitable for fixing joints, supports and channel structures for routing, protecting and distributing cables in electrical installations in industrial applications and large spans in: Oil & Gas and Petrochemical Industry, Power Plants, Electric Power Plants, etc. Water Treatment, Mining and Cement Offshore Platforms, Ports, Maritime Applications. Industrial projects in aggressive environments.

Solutions



Main technical characteristics

 GC

 Class 8

 M10

 100

 Steel with surface coating

 -50 / 150 °C

 A1 No combustible

ETIM 10
EC003861

Product data

	Ref	kg/u
20	67030059	0,023
35	67030077	0,029

 Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

 Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic