



Description

Pemsaband® Central Tray Joint for widths of 300, 400, 500 and 600 mm that provides the necessary strength at the joint. Width 300 mm, HDG finish. Manufactured in steel and available in GC or PG Protection System and steel AISI 304 and AISI 316.

Advantages

Provides the necessary strength in the connections of large width trays so that there is no deformation in the joint.

Available in various protection systems: PG, GC, BK8, AZ+ and stainless steel AISI 304 and AISI 316L.

Electrical continuity guaranteed according to standard IEC61537.

Its unique design allows the attachment to the Pemsaband® sheet tray lengths by using a part in the base.

Applications

Suitable for joining straight lengths of Pemsaband® One perforated and Solid tray of widths 300-600 mm, for the Support, management and distribution of Electrical and/or telecommunications cables in public buildings, infrastructures and civil works, tertiary sector and industrial applications.

Solutions



Product data			
ETIM 10	EC002413	u	10
Huella de CO2. GWP A1-A3 (kg CO2 eq.)	0,862	Material	Steel with surface coating
Protection System	GC	Working temperature range (°C)	-50 / 150 °C
Finish	HDG, Hot Dip Galvanised	Fire resistance	A1 No combustible
Resistance Class	Class 5		
Width (mm)	300		
kg/u	0,333		

🔒 Protection System

CU

- Copper electroplated

PG

- Pregalvanised

EZ

- Electrogalvanised

BC

- Electrogalvanised Bichromate

BK8

- High Resistance Coating

GC

- Hot Dip Galvanising

INOX

- Stainless Steel

PT

- Polyester Paint

AL

- Aluminum

LN

- Brass or Nickel-plated brass

🔒 Insulating materials

PC+ABS

- Halogen Free Polycarbonate + ABS

PVC

- Polyvinyl Chloride

PP

- Halogen Free Polypropylene

PA6

- Halogen Free Polyamide 6

PA12

- Halogen Free Polyamide 12

PU

- Polyurethane

PE

- Polyethylene

NBR

- NBR rubber

PET

- Thermoplastic Polyester

TPV

- Thermoplastic

Product applications





