



Description

Coupler for Metatray insulating trays. Of 100 mm height. This coupler has a click system, which makes it easy to install on the trays. Made of PVC with high corrosion resistance. Allows the joining of different sections of Metatray insulating trays.

Advantages

High anti-corrosion properties.

Insulating material, electrical safety and reduced maintenance costs.

Aenor N mark on product standards EN 61537 and EN 50085. CE compliance with directive 2014/35/EU.

Use with DIN603 M8 Metatray insulating screw kit. Ref 81000298.

Applications

Suitable for routing, transporting and distributing cables in electrical and/or telecommunications installations for charging electric vehicles, outdoor applications, renewable energies, chemical industry etc. as well as projects in aggressive and highly corrosive environments.

Solutions



Product data

ETIM 10	EC002413	Impact Strength (J)	6 J
Huella de CO2. GWP A1-A3 (kg CO2 eq.)	0,001	Working temperature range (°C)	-20 / 60 °C
Colour	Grey RAL 7035	Fire resistance	GRADO UL94: V0
Flange (mm)	100	UV Behaviour	Resistant acc. to UL568
kg/u	0,224		
u	10		
Material	PVC		

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic



Product applications







