

Pemsaband/Megaband Coupler (Ref: 93930003)

1/3



Description

Connector for joining cut sections of Pemsaband® tray and Megaband® ladder using M6 and M8 bolts and nuts. Of 100 mm height, HDG finish. Suitable for Pemsaband® tray and Megaband® ladder with heights of 35, 60, 85, 100 and 120 mm. Available in GC or PG Protection System.

Advantages

Suitable for Pemsaband® tray and Megaband® ladder in heights of 35, 60, 85, 100 and 120 mm.

Available in various protection systems: EZ, GC and stainless steel AISI 304 and AISI 316L.

Electrical continuity guaranteed according to standard IEC61537.

It allows the joining of cut straight sections.

Applications

Suitable for joining straight lengths of Pemsaband® One perforated, solid and Megaband® tray for the Support, management and distribution of Electrical and/or telecommunications cables in public buildings, infrastructures and civil works, tertiary sector and industrial applications.

Solutions



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



Product data

ETIM 10	EC002413	u	20
Huella de CO2. GWP A1-A3 (kg CO2 eq.)	0,312	Material	Steel with surface coating
Protection System	GC	Working temperature range (°C)	-50 / 150 °C
Finish	HDG, Hot Dip Galvanised	Fire resistance	A1 No combustible
Resistance Class	Class 6		
Flange (mm)	100		
kg/u	0,120		

Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic

PEMSABAND Couplers

10/10/2026

Pemsaband/Megaband Coupler (Ref: 93930003)

3/3

Product applications

□ □ □ □ □ □