

Coupler Pemsaband Vulcan



Description

Advantages

Applications

Solutions



Main technical characteristics

 PG3, Pregalvanised, ZM High Resistance Alloy	 12, 25, 50	 Steel with surface coating	 -50 / 150 °C	 A1 No combustible
ETIM 10				

Product data

				Ref	kg/u
PG	PG3, Pregalvanised	Class 3	12	82004955	0,079
PG	PG3, Pregalvanised	Class 3	25	82004957	0,095
PG	PG3, Pregalvanised	Class 3	50	82004958	0,147
AZ+	ZM High Resistance Alloy	Class 8	25	82004961	0,095
AZ+	ZM High Resistance Alloy	Class 8	50	82004962	0,147

 Protection System

- CU** - Copper electroplated
- PG** - Pregalvanised
- EZ** - Electrogalvanised
- BC** - Electrogalvanised Bichromate
- BK8** - High Resistance Coating
- GC** - Hot Dip Galvanising
- INOX** - Stainless Steel
- PT** - Polyester Paint
- AL** - Aluminum
- LN** - Brass or Nickel-plated brass

 Insulating materials

- PC+ABS** - Halogen Free Polycarbonate + ABS
- PVC** - Polyvinyl Chloride
- PP** - Halogen Free Polypropylene
- PA6** - Halogen Free Polyamide 6
- PA12** - Halogen Free Polyamide 12
- PU** - Polyurethane
- PE** - Polyethylene
- NBR** - NBR rubber
- PET** - Thermoplastic Polyester
- TPV** - Thermoplastic